

RUGGEDLINE IP67 ANTENNA RANGE A3010

ABOUT TIMES-7

Pushing the boundaries of RFID technology worldwide Times-7 are leaders in RFID antenna design and manufacture. Our patented award winning UHF antennas meet the needs of virtually any industry application; providing customers with fast accurate tracking of products, assets & people; empowering organizations to transform processes & reduce costs.

Our comprehensive range of antennas is unique in the RFID industry; offering high levels of performance & durability in an aesthetically superior form. Proven in a diverse & growing range of markets, applications include: retail & customer interaction, conference & people tracking, race timing, baggage handling, and logistic & supply chain asset management.

Authorized Reseller: RFID4UStore www.fid4ustore.com 1-408-739-3500 sales@rfid4ustore.com

Times-7 Research Ltd 29 Railway Avenue Lower Hutt 5010 New Zealand

NEW ZEALAND P: +64 4 974 6566

USA/CANADA P: +1 408 769 5025

E: info@times-7.com

www.times-7.com



The RuggedLine A3010

With 5dBic performance in a sleek yet ultra-rugged and compact 210x155mm (8" x 6") dimension, the A3010 is ideal for Forklift RFID and proven in applications from waste management to access control. Impact strengthened, the RuggedLine IP67 range is rated for 24/7 outdoors and all weather use. Available in a flush or rack mount configuration, Times-7's RuggedLine antennas are setting a new benchmark for high performance RFID in demanding/industrial applications.

Specifications

Physical / Environmental Specifications

Dimensions (L x W x D):	210 mm x 155 mm x 14 mm	
	8.3 " x 6.1 " x 0.55 "	
Weight:	0.75 kg (1.6 lbs)	
Radome Material:	PPE	
Environmental Rating:	IP67	
Operating / Storage Temperature:	-20° to +55°C / -30° to +65°C	
	-4° to +131°F / -22° to +149°F	
Mounting:	Flush mount standard, rack mount accessory available	
Connector type / position:	1 m 195 cable with RP-TNC connector	

Electrical Specifications


Frequency Range:	864-869 MHz / 902-928 MHz
Polarisation:	Circular
Far-field Gain:	5 dBiC Peak
Far-field 3 dB beamwidth:	XZ = 70° YZ = 90°
Typical VSWR across frequency range:	< 1.4 across the band
Front to back ratio:	-13 dB
Axial ratio:	<2.5 dB Typical
Nominal Impedance:	50 Ω
Anti-static protection:	Yes
Maximum Input Power:	6 W






RUGGEDLINE IP67 ANTENNA RANGE A3010

E-field elevation & Azimuth Patterns





Vertical

Ordering Information (please quote both product code & part no.)

Product Code	Band	Part No.
A3010	902-928 FCC	71655
A3010	864-869 ETSI	71658
Rack Mount Accessory		71757
Cable Accessories	Cable Type	Part No.
Cable Accessories Cable 2 m, SMA to RPTNC	Cable Type 195 / 240	Part No. 71436 / 71782
	2.	

Applications

- Warehousing
- Access Control / Vehicle Tolling
- Waste management







The technical data contained in this publication is not a guarantee for which Times-7 Research Ltd assumes legal accountability. It is indicative of typical performance, and if required should be relied on for specific applications only after due verification.

All technical data, specifications and other information contained herein are deemed to be the proprietary intellectual property of Times-7 Research Ltd. No reproduction, copy or use thereof may be made without the express written consent of Times-7 Research Ltd.

OUR GLOBAL NETWORK

Constantly increasing market reach and influence in the global RFID industry, Times-7's international support spans The Americas, Europe, and Asia Pacific regions through our distributor, authorized reseller and integrated solutions provider network.



Authorized Reseller: RFID4UStore www.rfid4ustore.com 1-408-739-3500 sales@rfid4ustore.com

Times-7 Research Ltd 29 Railway Avenue Lower Hutt 5010 New Zealand

> NEW ZEALAND P: +64 4 974 6566

USA/CANADA P: +1 408 769 5025

E: info@times-7.com

www.times-7.com



Times-7, and the stylized T-7 Antennas logo are trademarks or registered trademarks of Times-7 Research Ltd. All other trademarks are the property of their respective owners. © 2017 Times-7 Research Ltd. All rights reserved. Specifications are subject to change without notice. Datasheet v1.4