

CS772 Linear RFID Far Field Antenna

Product Profile:

CS772 is a linear polarized UHF RFID Far Field antenna for long range operation where the tag polarization is known and controllable. The antenna connects via a 3 meter cable to a TNC Reverse Polarity plug connector that is compatible with CS461 fixed reader.



Features:

- Single Antenna Element
- Linear Polarization
- Excellent matching for best RFID read performance
- Ruggedized operation

Specifications:

Physical Characteristics:	Length: 30 cm; Width: 30 cm; Height: 4 cm; Weight = 5 lbs
Mounting:	2 x 2 mounting stud, horizontal separation 5.875 inches, vertical separation 2.75 inches, 1/4 x 0.625 inch studs with 20 threads/inch threading
Environment:	Operating Temp: -20°C to 55°C (-4°F to 131°F) Storage Temp: -40°C to 85°C (-40°F to 185°F) Humidity: 5% to 95% Non-condensing
Frequency Range:	One of the following: 865-868 MHz, 865-867 MHz, 902-928 MHz, 952-954 MHz
Polarization:	Linear
Peak Gain:	9 dBi
Front-to-Back Ratio:	20 dB
Beamwidth:	54 degrees
Impedance:	50 ohms
Return Loss:	Better than 20 dB down
Input Power:	10 Watts
ESD:	10 KV (no ESD sensitive component)
Order Code:	CS772C-024-N (N=1: 865-868 MHz for Europe & 865-867 MHz for India, N=2: 902-928 MHz, C=S:SMA Reverse Polarity Connector, C=N:N Reverse Polarity Connector, C={none}: TNC Reverse Polarity Connector, 024=standard 2.4m cable and please discuss with CSL sales department for special requirements)



Authorized Reseller:
RFID4UStore
www.rfid4ustore.com
1-408-739-3500
sales@rfid4ustore.com

CHUNG NAM BUILDING,
20th Floor,
No. 1 Lockhart Road,
Wanchai
Hong Kong

TEL: (852) 25293008

FAX: (852) 26832018

WEBSITE:

www.convergence.com.hk