

Ultra-Rugged UHF RFID Tag


UHF RFID Tag WT-A521/A522

Wash, Rinse,
Track, Repeat.

Ultra-Rugged UHF RFID Tags for Commercial and Industrial Textile Applications

- ▶ UHF technology to read hundreds of tags simultaneously
- ▶ More than 6 foot reading distance
- ▶ Cost efficient solution with exceptional durability for washing, drying, dry cleaning and ironing
- ▶ Suitable for high-pressure extractors up to 60 bar
- ▶ Small, soft, flexible material ideal for textiles, linens, garments and accessories
- ▶ Conforms to "ISO/IEC 18000-6 Type C"
- ▶ 100% non-magnetic construction, suitable for hospital use




FUJITSU

Wash, Rinse,
Track, Repeat.

UHF RFID Tag WT-A521/A522

Fujitsu's Flexible RFID Tags

Businesses can take advantage of the new ultra-rugged Fujitsu A521/A522 flexible and washable RFID tags to manage their textile, linen and garment assets. Combining the efficiency of check-at-once inventory management with the extended range and accuracy of state-of-the-art UHF tag technology, customers will greatly improve receiving, shipping, and tracking assets while keep their costs low by improving workflow and efficiency.

Advantages of UHF Technology

Speed

UHF efficiency increases tag read performance to read hundreds of tags in a single pass.

Rugged

Can withstand high pressure extractors and flatworks irons used in high-throughput laundries

Accuracy

Inventory management can be performed accurately and easily by reading multiple tags with very low error rates.

ROI

Installation of UHF technology will provide cost-effective garment management by reducing labor cost associated with barcode or high frequency RFID tags.



Specifications			
Model	Fujitsu RFID Tag WT-A521 Fujitsu RFID Tag WT-A522		
RFID Standard	ISO/IEC 18000-6 TypeC (EPC Gen2)		
Size & Weight	55(W)x10(D)x1.6(H)mm, 1g		
EPC Number Area	96bit permanent locked	96bit password locked	
User Memory	512 bits		
Reading Range	902-928MHz	4W eirp : 250 cm (Typical) 2W erp : 220 cm (Typical)	
	865.6-867.7 MHz	2W erp : 200 cm (Typical)	
Tagging	Sewing, Heat-sealing		
Estimated Lifetime	200 washing cycles or 3 years, whichever comes first		
Estimated Failure Rate	0.1% excluding DOA *1		
Environmental Resistance	Washing Method	Laundry, Dry cleaning*2 (Perchloroethylene, Hydrocarbon solvent)	
	WaterExtraction Pressure	60 bar *3	
	Water Resistance	Water resistant	
	Chemical Resistance	Detergent, Softener, Bleach (Oxygen/ Chlorine), Alkali *4	
	Autoclave Heat Sterilization	121 °C for 15-20 minutes - 100 cycles	
	Heat Resistance	Drying	85 °C (Up to 60min.) or 120 °C (Up to 10 min.)
		Ironing	200 °C (Up to 10 sec. with press cloth)
Humidity/ Temperature	Operating	-20 to 50 °C, 10 to 95% RH	
	Storage	-40 to 55 °C, 8 to 95% RH	

All data are results performed in our test condition according to Japan Industrial Standard JIS L 0217 - 102, 301, 401, 402. Your test result may vary.

*1: Excludes appearances (discoloration, bending, distortion, etc.) due to normal use

*2: Conditions for dry cleaning: Up to 10min./cycle (Washing), More than 30min./cycle within 60°C (Drying)

*3: Tested in Fujitsu Laundry testing conditions - 100 cycles

*4: The tag has been tested for 10 times at the condition of JIS L 0856 Severe test.

Installation Notes:

Do not attach near metal objects



Fujitsu Frontech North America, Inc.
<http://www.fujitsufrontechna.com>
27121 Towne Centre Drive, #100 Foothill Ranch, CA. 92610

©Copyright 2012 Fujitsu Frontech North America Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks. All other trademarks are the property of their respective owners. Statements herein are based on normal operating conditions and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Frontech North America Inc. reserves the right to modify at any time without notice these statements, our services, products, and their warranty and performance specifications.



Authorized Reseller:
RFID4UStore
www.rfid4ustore.com
1-408-739-3500
sales@rfid4ustore.com

