

ROBUST LOW, HIGH AND ULTRAHIGH FREQUENCY RFID TAGS THAT PERFORM IN TOUGH CONDITIONS

- **Durable** - built to withstand the rigors of industrial processing, transportation and outdoor use
- **Versatile** - mounts anywhere without compromising performance: glass, plastic, or wood, with options for on metal mounting
- **Diverse selection** - broad spectrum of available frequencies, memory sizes and diameters with multiple fixation methods

IN Tag™ passive contactless RFID transponders are highly water, chemical and shock resistant, ATEX certified for use in explosive environments, withstand peak temperatures up to 285° F (140° C) and are UL94-HB flame resistant.

Low frequency (LF) IN Tag discs perform well affixed to virtually any surface. They offer reliable, cost-effective tagging for near-proximity reader applications, with data storage from a 64-bit user ID, up to 2048-bit read-write capability.

High frequency (HF/NFC) discs offer anti-collision technology for faster data processing, larger memory storage, and improved read ranges. HF IN Tag devices are available with up to 1 kbit EEPROM or 8 kilobyte FRAM - the highest memory specified by ISO/IEC 15693. FRAM tags are radiation resistant to survive Gamma sterilization and offer an exceptional speed with up to 10 billion write cycles.

Ultrahigh frequency (RAIN® UHF) IN Tag RFID tags can be read from up to 9.8 ft (3 m). Entire pallets of individual containers or equipment may be identified and item level status updated, as articles roll through distribution and receiving points. They are compliant to EPC Global Class 1 Gen 2 standards and readers.

HID IN Tag RFID tags come in a variety of sizes. For LF and HF applications, tiny 0.79 in (20 mm) discs may be glued or embedded virtually anywhere. If a larger read range is required, HID offers 1.18 in (30 mm) and 1.97 in (50 mm) options, which include pre-drilled holes for screw attachment. UHF tags come in 1.97 in (50 mm) and 2.17 in (55 mm) discs.

HID IN Tag transponders are an excellent performance-level tag. For lighter-duty applications, consider HID Epoxy Disc or World Tag™ transponders.

TECHNOLOGY HIGHLIGHTS:

- Low Frequency (125 kHz), up to 2048 bit read-write memory
- High frequency (13.56 MHz), up to 8 kilobyte read-write memory
- Ultrahigh frequency (865 to 915 MHz), 240 bit EPC, 640 bit read-write memory
- Food compatible
- Flame and UV resistant
- Disc diameters of 20, 30, 50 mm (55 mm with spacer)
- Optional configurations for mounting on metal



IN Tag™




SPECIFICATIONS

		IN Tag™					
		Low Frequency - LF					
		200		300		500	
Base Model Number		623182	601182	623183	624183	601183	624185
ELECTRONIC							
Operating Frequency		125 kHz					
Chip Type		HITAG S	Unique	HITAG S	Unique	HITAG S	Unique
Memory		256 bit EEPROM	64 bit read-only	256 bit EEPROM	2048 bit EEPROM	64 bit read-only	2048 bit EEPROM
Anti-collision		Yes		Yes		Yes	
Reading Distance 2 W reader ERP, free space		Dependent upon reader, environment and application					
PHYSICAL							
Dimensions		Ø 0.79 x 0.12 in (Ø 20 x 3 mm)		Ø 1.18 x 0.12 in (Ø 30 x 3 mm)		Ø 1.97 x 0.12 in (Ø 50 x 3 mm)	
Mounting Method		Embed, glue		Embed, glue, screw			
Fixation Hole Size		Ø 0.20 in (5.2 ± 0.3 mm)					
Affixes To		Glass, plastic, wood, metal					
Housing Material		PPA Polyphthalamide [ISO 1874: PA6T/6I-GF50]					
Color		Black					
Weight		0.04 oz (1.3 g)		0.11 oz (3 g)		0.34 oz (9.5 g)	
CHEMICAL AND MECHANICAL							
Water		IP68, IP69K, 176° F (80° C), 100 bar, 30 sec. 16 l/min					
Withstands Exposure To		Fuel B, mineral oil, petroleum, salt mist, vegetable oil, [UV resistant ISO 4892-2], [food compatible, directive 02/72/EC], [flame resistant UL94-HB]*					
Environmental Test Conditions		68° F (20° C), 100 h					
Vibration		IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]					
Shock		IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]					
Drop Test		100 x 5.9 ft (1.8 m)					
Axial / Radial Force		800 N / 500 N, 10 sec.					
THERMAL							
Storage		-40° to +194° F (-40° to +90° C), 1000 h					
Operating		-13° to +185° F (-25° to +85° C)					
Shock/Fatigue		-40° to +194° F (-40° to +90° C) 50x5 min with 30 sec transition					
Peak		284° F (140° C), 100 h					
OTHER							
Standards		EN 60079-0:2009; EN 60079-11:2007; EN 60079-26:2007					
Box Size		1500 pcs		750 pcs		250 pcs	
Options		Custom embossed, printed or no logo					
Warranty		2 Years					



HID can create a custom tag solution to fit your application requirements for chip type, dimensions, programming and materials.















*Flame Resistance UL94-HB not applicable for spacer of INTag 500 OM or INTag 500 UHF OM.

INDUSTRY AND LOGISTICS:

- **Asset tracking and logistics**
 - Tool and equipment inventory
 - Maintenance management
- **Automation and manufacturing**
 - Process automation
 - Real-time materials inventory
 - Food processing
- **Returnable transport items**
 - Inventory and distribution tracking
 - Container maintenance
- **Waste management**
 - Bin tracking
 - Recycling compliance monitoring
 - Improved invoicing and service accuracy
 - Route optimization
 - Incentive-based waste and recycling programs

SPECIFICATIONS

	IN Tag™											
	High Frequency - HF								Ultrahigh Frequency - RAIN UHF			
	200	300	500	500 OM	200	300	300 8KB	500	500 EU	500 EU OM	500 US	500 US OM
												
Base Model Number	629182-012 629182-013 (FOAM)	629183-012 629183-312	629185-312	629185-301	634182	634183	6D1183-010	634185	6E5185-010	6E5185-310	6E5186-010	6E5186-310
ELECTRONIC												
Operating Frequency	13.56 MHz								865 MHz (EU)		915 MHz (US)	
Chip Type	ICODE SLIX 2				F-Mem				G2IM			
Memory	ICODE SLIX - 896 Bit User Memory ICODE SLIX2 - 2560 Bit User Memory				2 Kbyte FRAM		8 Kbyte FRAM	2 Kbyte FRAM	640 bit EEPROM (96 bit TID, 256 bit EPC)			
Anti-collision	Yes											
Reading Distance 2 W reader ERP, free space	Dependent upon reader, environment and application								Up to 9.8 ft (3 m)			
PHYSICAL												
Dimensions	Ø 0.79 x 0.12 in (Ø 20 x 3 mm)	Ø 1.18 x 0.12 in (Ø 30 x 3 mm)	Ø 1.97 x 0.12 in (Ø 50 x 3 mm)	Ø 2.17 x 0.51 in (Ø 55 x 13 mm)	Ø 0.79 x 0.12 in (Ø 20 x 3 mm)	Ø 1.18 x 0.12 in (Ø 30 x 3 mm)	Ø 1.97 x 0.12 in (Ø 50 x 3 mm)	Ø 1.97 x 0.14 in (Ø 50 x 3 mm)	Ø 1.97 x 0.14 in (Ø 55 x 13 mm)	Ø 2.17 x 0.51 in (Ø 55 x 13 mm)	Ø 1.97 x 0.14 in (Ø 50 x 3 mm)	Ø 2.17 x 0.51 in (Ø 55 x 13 mm)
Mounting Method	Embed, glue	Embed, glue, screw			Embed, glue	Embed, glue, screw						
Fixation Hole Size	Ø 0.20 in (5.2 ± 0.3 mm)				Ø 0.20 in (5.2 ± 0.3 mm)							
Affixes To	Glass, plastic, wood			Metal, glass, plastic, wood	Glass, plastic, wood				Glass, plastic, wood	Metal, glass, plastic, wood	Glass, plastic, wood	Metal, glass, plastic, wood
Housing Material	PPA Polyphthalamide [ISO 1874: PA6T/6I-GF50]											
Color	Black											
Weight	0.04 oz (1.3 g)	0.11 oz (3 g)	0.34 oz (9.5 g)	1.06 oz (30 g)	0.04 oz (1.3 g)	0.11 oz (3 g)	0.34 oz (9.5 g)	0.35 oz (9.5 g)	1.27 oz (36 g)	0.35 oz (9.5 g)	1.27 oz (36 g)	1.27 oz (36 g)
CHEMICAL AND MECHANICAL												
Water	IP68, IP69K, 176° F (80° C), 100 bar, 30 sec. 16 l/min											
Withstands Exposure To	Fuel B, mineral oil, petroleum, salt mist, vegetable oil, [UV resistant ISO 4892-2], [food compatible, directive 02/72/EC], [flame resistant UL94-HB]*											
Environmental Test Conditions	68° F (20° C), 100 h											
Vibration	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]											
Shock	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]											
Drop Test	100 x 5.9 ft (1.8 m)											
Axial / Radial Force	800 N / 500 N, 10 sec.											
THERMAL												
Storage	-40° to +194° F (-40° to +90° C), 1000 h											
Operating	-40° to +185° F (-40° to +85° C)				-13° to +185° F (-25° to +85° C)				-40° to +185° F (-40° to +85° C)			
Shock/Fatigue	-40° to +194° F (-40° to +90° C), 50x5 min with 30 sec transition											
Peak	284° F (140° C), 100 h											
OTHER												
Standards	EN 60079-0:2009, EN 60079-11:2007, EN 60079-26:2007; ISO 15693, ISO 18000-3								ISO 18000-6C, EPC C1G2 EN 60079-0:2009; EN 60079-11:2007; EN 60079-26:2007			
Box Size	1500 pcs	750 pcs	250 pcs	50 pcs	1500 pcs	750 pcs	750 pcs	250 pcs	250 pcs	50 pcs	250 pcs	50 pcs
Options	Custom embossed, printed or no logo											
Warranty	2 Years											

North America: +1 512 776 9000 • Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +44 1440 714 850
Asia Pacific: +852 3160 9800 • Latin America: +52 55 5081 1650

© 2017-2019 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design and IN Tag are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

2019-10-23-hid-rfid-il-in-tag-family-ds-en

PLT-00276

An ASSA ABLOY Group brand

ASSA ABLOY



hidglobal.com



Authorized Reseller:
RFID4UStore
www.rfid4ustore.com
1-408-739-3500
sales@rfid4ustore.com