



MT-120018/A MOUNTING KIT FOR FLAT PANEL ANTENNA



CONSTRUCTION

INSTALLATION METHOD	Pole size $\varnothing 1\text{''} \pm \varnothing 3\text{''}$ or wall
AZIMUTH RESOLUTION STEP	2° on wall
TILT RESOLUTION STEP	2° on pole and wall
WEIGHT	0.86 kg
PAY LOAD	20 kg (max)
MATERIALS	
BRACKETS	AL.AL. LM2-T6 with chemical conversion coating
CLAMPS	AL.AL. LM2-T6 with chemical conversion coating
FASTENERS	Steel zinc plated

ADD TO COMPARISON | COMPARE

ENVIRONMENTAL

TEMPERATURE	-55°C +71°C
VIBRATION	IEC 60721-3-4 4M5 Random
SHOCK MECHANICAL	IEC 60721-3-4 4M5
HUMIDITY	0-100%
ICE LOADING	25 mm Radial
SALT FOG	IEC 68-2-11 Ka, 500h
WIND LOAD (SURVIVAL) FRONT THRUST SIDE THRUST	47 kg (103.4 lbs) 6 kg (13.2 lbs)
INSTALLATION INSTRUCTION DOCUMENT	RD41169300C RD41169400C

*(1) THIS REFLECTS SURVIVAL WIND SPEED OF 220 Km/H AND OPERATION WIND SPEED OF 160 km/h .

(2) FOR ANTENNA OF 450×450 mm THIS WIND LOAD (SURVIVAL) IS:

FRONT THRUST: 56 Kg

SIDE THRUST : 5 Kg

AT WIND SPEED ABOVE 188 km/h SOME ANT. ADJUSTMENT WIL BE REQUIRED.

WAIVER!

While the information contained in this document has been carefully compiled to the best of our present knowledge, it is not intended as presentation or warranty of any kind on our part regarding the fitness of the products concerned for any particular

2/21/2014

MTI Wireless Edge – One stop shop for YOUR antenna needs

intended as presentation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

MTI Wireless Edge Ltd.

11 Hamelacha St. Afek Industrial Park Rosh Ha'ayin 48091, Israel
Tel: +972-3-9008900 | Fax: +972-3-9008901 | www.mtiwe.com

