

TagMatiks RFID Cable Tag



AvailableOn



Ordering Information

SKU: TMCBLHXXX Frequency: 860-960 MHz (EU, US, JP)

01 When should I use TagMatiks Cable Tags?

The TagMatiks Autoclave Tolerant Tags are best used for applications for tracking assets that cables. There are a wide variety of

02 Why pre-printed/pre-encoded?

Leverage pre-printed and pre-encoded tags to simplify RFID tag and asset pairing (also known as commissioning) with TagMatiks. For ease of use, the same unique number is not only encoded into the RFID tag but also printed in human readable text and barcode formats.

03 Why are there different sizes for the cable holders?

The different sizes for the cable holders designed for cables for different sizes.

Sizes Available

- 0.700 inches
- 0.880 inches
- 1.10 inches
- 0.3 inches
- 0.54 inches
 - 1.312 in





NEED HELP WITH YOUR SOLUTION OR MORE DETAILS? CONTACT US!

TagMatiks RFID Cable Tag

SKU: TMCBLHXXX Frequency: 860-960 MHz (EU, US, JP)

Contact

- **(**408) 739-3500
- sales@rfid4ustore.com
- orfid4ustore.com



Location

- § 5159 Commercial Circle,
 - Suite H, Concord, CA, 94520
- **Radio Frequency Specification**
- **Air Protocols**
- **Operating Frequency**
- IC Type
- User Memory
- **EPC Memory**
- Read Range

- ISO 18000-6C
- 860-960 MHz (EU, US, JP)
- Higgs 3
- 512 bit
- 96 bit
- Usually 3 4 M / 9ft 12ft

Physical Specification

Attachment Method	-	Adhesive
Operating Temperatures	-	-40°C to +70°C (-40°F to +158°F)
Dimensions	-	3.4 x 1.0 x 0.1 inches (87 x 25 x 3 mm)