

Versa Trak II



Functional Specifications

RF air protocol	EPC Class 1 Gen 2; ISO18000-6C
Operating frequency	UHF 902-928 MHz (US); 866-868 MHz (EU)
IC type	Alien Higgs-3
Memory configuration	96-bit EPC ; 512-bit user memory; 64-bit TID
Functionality	Read / write (user programmed); full duplex protocol
Memory – expected read / write cycles	100,000 cycles at 77°F (25°C)
Data retention	Up to 50 years ¹
Read rate	400 tags per second for 96-EPC bit number
Warranty(limited)	1 year

Performance Characteristics

Read range on-metal (2W ERP) ²	Up to 26 ft (8 m)
Read range off-metal (2W ERP) ²	Up to 13 ft (4 m)
Polarization	Linear

Physical Specifications

Material	Anti-UV Industry Grade Polymer
Mounting system	Rivet hole, ø 0.14 in (3.5 mm), adhesive (optional) Cable tie
Color	Cool gray

Environmental and Industry Compliance



RoHS	EU Directive 2011/65/EU
------	-------------------------



¹ The chip data retention is based on chip operating under general environment conditions.

² Actual read range may vary based upon use case and antenna power.

Radiation Pattern



Operational and Environmental Specifications

Operational temperature

Cold	-40°F (-40°C)
Dry heat (Long term, days/weeks/years)	+185°F (+85°C)
Thermal shock	-22°F to 185°F (-30°C to +85°C); cycled

Application temperature

Cold	-40°F (-40°C)
Dry heat (Short term, minutes/hours)	+185°F (+85°C)

Humidity

Operational humidity	5%-95% non-condensing
Storage humidity	5%-95% non-condensing

Shock (drop)

3 ft (1 m) to concrete/granite up to 200 cycles

Vibration

MIL-STD-810F



Compression strength

26.1 psi (180 kPa)

IP classification

IP68

Product Dimensions and Weight



Dimensions (mm)

73.3 x 22.8 x 8.3

tolerance

+/- 0.5

Dimensions (in)

2.88 x 0.9 x 0.33

tolerance

+/- 0.02

Weight

0.39 oz (11 g)

Order information

X0351-US100-H3

Versa Trak II US

X0351-EU100-H3

Versa Trak II EU